

RENNER screw compressor

Type RS 3,0 – 132,0 D

Technische Daten

Type	free air delivered f.a.d. m ³ /min at:				motor power		dimensions width x depth x height mm	weight kg
	7,5 bar	10 bar	13 bar	15 bar	kW	HP		
RS 3,0	0,41	0,32	0,24	0,21	3,0	4,0	567 x 764 x 900	160
RS 4,0	0,56	0,46	0,35	0,30	4,0	5,5	567 x 764 x 900	160
RS 5,5	0,77	0,65	0,53	0,45	5,5	7,5	567 x 764 x 900	170
RS 7,5	1,10	0,95	0,74	0,63	7,5	10,0	567 x 764 x 900	180
RS 9,0	–	1,09	0,86	0,76	9,0	12,0	567 x 764 x 900	190
RS 11,0	1,76	1,50	1,16	0,93	11,0	15,0	664 x 992 x 1117	270
RS 15,0	2,24	1,96	1,51	1,24	15,0	20,0	664 x 992 x 1117	290
RS 18,5	2,91	2,62	2,20	1,89	18,5	25,0	791 x 1281 x 1290	480
RS 22,0	3,46	3,10	2,66	2,31	22,0	30,0	791 x 1281 x 1290	510
RS1-30,0	4,38	4,01	3,52	3,02	30,0	40,0	791 x 1281 x 1290	550
RS2-30,0	5,05	4,28	3,76	3,40	30,0	40,0	931 x 1392 x 1575	680
RS 37,0	6,15	5,24	4,56	4,15	37,0	50,0	931 x 1395 x 1575	730
RS 45,0	7,25	6,51	5,55	5,03	45,0	60,0	931 x 1392 x 1575	830
RS 55,0	9,30	7,96	6,70	5,87	55,0	75,0	1110 x 1505 x 1575	980
RS 75,0	12,35	10,55	9,40	8,30	75,0	100,0	920 x 2100 x 1813	2200
RS1-90,0	14,56	13,05	11,70	10,20	90,0	120,0	920 x 2100 x 1813	2250
RS2-90,0 D	15,36	13,53	11,00	10,49	90,0	120,0	1460 x 2880 x 1980	2800
RS 110,0 D	17,50	16,10	13,52	11,86	110,0	150,0	1460 x 2880 x 1980	2950
RS 132,0 D	21,56	19,35	15,60	14,04	132,0	180,0	1460 x 2880 x 1980	3100