

# RS - F range

screw compressors  
with frequency regulation  
from 11 Kw to 75 kW

## Technical data :

Type	free air delivered f.a.d.m <sup>3</sup> /min at:				motor power		dimensions width x depth x height	weight kg
	7,5 bar	10 bar	13 bar	15 bar	kW	HP		
RS-F 11.0	0,52 - 1,76	0,45 - 1,50	0,35 - 1,16	0,28 - 0,93	11,0	15,0	660 x 1280 x 995 mm	340
RS-F 15.0	0,67 - 2,24	0,59 - 1,96	0,45 - 1,51	0,37 - 1,24	15,0	20,0	660 x 1280 x 995 mm	350
RS-F 18.5	0,87 - 2,91	0,79 - 2,62	0,66 - 2,20	0,57 - 1,89	18,5	25,0	790 x 1560 x 1220 mm	570
RS-F 22.0	1,04 - 3,46	0,93 - 3,10	0,80 - 2,66	0,69 - 2,31	22,0	30,0	790 x 1560 x 1220 mm	600
RS-F1-30.0	1,31 - 4,38	1,20 - 4,01	1,06 - 3,52	0,91 - 3,02	30,0	40,0	790 x 1560 x 1220 mm	640
RS-F2-30.0	1,52 - 5,05	1,28 - 4,28	1,13 - 3,76	1,02 - 3,40	30,0	40,0	940 x 1875 x 1490 mm	810
RS-F 37.0	1,85 - 6,15	1,57 - 5,24	1,37 - 4,56	1,25 - 4,15	37,0	50,0	940 x 1875 x 1490 mm	860
RS-F 45.0	2,18 - 7,25	1,95 - 6,51	1,67 - 5,55	1,51 - 5,03	45,0	60,0	940 x 1875 x 1490 mm	960
RS-F 55.0	2,79 - 9,30	2,39 - 7,96	2,01 - 6,70	1,76 - 5,87	55,0	75,0	1100 x 1900 x 1580 mm	1130